MONZA

PRODUCT DATA SHEET
REV. 1 · 2026-11-14

Prima CI-4 SAE 15W-40

HEAVY DUTY DIESEL ENGINE OIL

DESCRIPTION

MONZA Prima CI-4 SAE 15W-40 is a premium multigrade heavy-duty diesel engine oil for modern high-speed four-stroke engines. It is formulated for the higher soot loads and temperatures of engines with exhaust gas recirculation (EGR), with strong oxidation stability, deposit control and wear protection, and the 15W-40 grade gives fast oil flow at start-up.



5 L 20 L

API SERVICE	SAE GRADE
CI-4	**15W-40**

PACK SIZES
5 L · 20 L

APPLICATIONS

- High-speed four-stroke diesel engines where API CI-4 is recommended, including EGR-equipped engines designed for 2004 emission standards
- Engines where earlier categories such as API CH-4, CG-4 or CF-4 are recommended
- Long-haul trucks, coaches and buses
- Construction, mining and agricultural equipment

FEATURES & BENEFITS

- Handles high soot loads from EGR engines without thickening
- High alkaline reserve (TBN 12) for extended protection against acids
- High viscosity index (129) and low pour point (-27 °C) for fast start-up flow
- Excellent foam control in all three test sequences

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	UNIT	TYPICAL
SAE viscosity grade	**SAE J300**	—	**15W-40**
Kinematic viscosity at 40 °C	ASTM D445	mm²/s	**125.1**
Kinematic viscosity at 100 °C	ASTM D445	mm²/s	**15.45**
Viscosity index	ASTM D2270	—	**129**
Flash point (COC)	ASTM D92	°C	**238**
Pour point	ASTM D97	°C	**–27**
Total base number (TBN)	ASTM D2896	mg KOH/g	**12**
Foam tendency / stability, sequences I · II · III	ASTM D892	ml	**0/0 · 0/0 · 0/0**

Typical values are from production testing (2026-09-21) and represent current production. They are not a specification; normal manufacturing variation applies.

STORAGE & HANDLING

Store packs under cover, away from direct sunlight and sources of heat, between 0 °C and 50 °C. Keep containers closed when not in use to prevent contamination by water and dust. Do not mix with other oils.

HEALTH, SAFETY & ENVIRONMENT

Unlikely to present a significant hazard when used as recommended. Avoid prolonged skin contact and wash with soap and water. Take used oil to an authorised collection point; do not discharge into drains, soil or water. Safety data sheet available on request.

MONZA

MONZA is a lubricants brand of ENERGZ
energz.net/monza · info@energz.net
+20 100 847 6484 · +20 109 997 0036

Always follow the vehicle or equipment manufacturer's recommendations for oil grade, specification and drain interval. The information in this data sheet is given in good faith and is accurate to the best of our knowledge at the date of issue; it may change without notice as products are developed. Check energz.net/monza for the current version.